

Model	: FP2SS 6322 B5 TENV
Type	: 3 Phase asynchronous
Rotor type	: Aluminium Squirrel Cage
Number of pole's	: 2
Power	: 0,25 kW
Voltage	: 230V / 400V +/-10%

50 Hz**60 Hz**

	50 Hz	60 Hz
Speed	2850 min-1	3420 min-1
Current	230V Δ 1,13 A 400V Y 0,65 A	276V Δ 0,94 A 480V Y 0,55 A
Efficiency	76,7 %	76,7 %
Power factor cos φ 100%	0,73	0,73
Tn (Nominal Torque)	0,84 Nm	0,70 Nm
Ts (Starting Torque)	3,17 Nm	2,65 Nm
Tmax (Maximum Torque)	3,61 Nm	3,01 Nm
Is (Starting Current)	230V Δ 6,90 A 400V Y 3,90 A	276V Δ 5,70 A 480V Y 3,40 A

Weight:	: 8,7 Kg
IE class	: IE2
IP class	: IP66
Isolation class	: F (155°C)
Delta K	: 72 K
IEC frame	: IEC 63
Execution type	: B5 (Flange 140mm)
Shaft Dimensions	: Ø 11 j6 x 23 mm
Cooling	: TENV - IC410 (Totally Enclosed Non Ventilated)
Duty Cycle:	: S1 100%
Housing material	: Stainless Steel AISI 304
Bearingshield material	: Stainless Steel AISI 304
Shaft material	: Stainless Steel AISI 304 (With Dertec TTS)
Oil seal material	: High Temperature NBR
Bearings	A Side (Shaft side) : 6201 2RS C3 With HTWR Foodgrade Grease B Side (Fan Side) : 6201 2RS C3 With HTWR Foodgrade Grease
Cable gland bore	: 2 x M20 for cable Ø between 8 - 12mm)
Cable gland material	: Stainless Steel AISI 304
Thermal protection	: PTC 135 (PTC) : PT1 135 (Clixon / Thermal contact)
Certification	: UL & CE
Taric Code	: 8501200090
Country of origin	: The Netherlands