

Model	: FP2SS 132S22 B14A TEFC
Type	: 3 Phase asynchronous
Rotor type	: Aluminium Squirrel Cage
Number of pole's	: 2
Power	: 7,5 kW
Voltage	: 400V / 690V +/-10%

50 Hz**60 Hz**

	50 Hz	60 Hz
Speed	2920 min-1	3500 min-1
Current	400V Δ 13,3 A 690V Y 7,70 A	480V Δ 11,1 A 840V Y 6,40 A
Efficiency	90 %	90,0 %
Power factor cos φ 100%	0,91	0,91
Tn (Nominal Torque)	24,5 Nm	20,5 Nm
Ts (Starting Torque)	55,0 Nm	45,0 Nm
Tmax (Maximum Torque)	61,0 Nm	52,0 Nm
Is (Starting Current)	400V Δ 93,0 A 690V Y 54,0 A	480V Δ 78,0 A 840V Y 45,0 A

Weight:	: 80,0 Kg
IE class	: IE3
IP class	: IP66
Isolation class	: F (155°C)
Delta K	: 52 K
IEC frame	: IEC 132
Execution type	: B14A (Flange 200mm)
Shaft Dimensions	: Ø 38 j6 x 80 mm
Cooling	: TEFC - IC411 (Totally Enclosed Fan Cooled)
Duty Cycle:	: S1 100%
Housing material	: Stainless Steel AISI 304
Bearingshield material	: Stainless Steel AISI 304
Shaft material	: Stainless Steel AISI 304 (With Dertec TTS)
Oil seal material	: High Temperature NBR
Bearings	A Side (Shaft side) : 6308 2RS C3 With HTWR Foodgrade Grease B Side (Fan Side) : 6308 2RS C3 With HTWR Foodgrade Grease
Cable gland bore	: 2 x M25 for cable Ø between 11 - 15mm)
Cable gland material	: Stainless Steel AISI 304
Thermal protection	: PTC 135 (PTC) : PT1 135 (Clixon / Thermal contact)
Certification	: UL & CE
Taric Code	: 8501200090
Country of origin	: The Netherlands