

Model	: FP2SS 90S6 B5 TEFC
Type	: 3 Phase asynchronous
Rotor type	: Aluminium Squirrel Cage
Number of pole's	: 6
Power	: 0,75 kW
Voltage	: 230V / 400V +/-10%

	50 Hz	60 Hz
Speed	960 min-1	1150 min-1
Current	230V Δ 3,24 A 400V Y 1,90 A	276V Δ 2,70 A 480V Y 1,56 A
Efficiency	83,0 %	83,0 %
Power factor cos φ 100%	0,70	0,70
Tn (Nominal Torque)	7,46 Nm	6,22 Nm
Ts (Starting Torque)	15,0 Nm	12,5 Nm
Tmax (Maximum Torque)	17,0 Nm	14,5 Nm
Is (Starting Current)	230V Δ 16,0 A 400V Y 9,50 A	276V Δ 13,5 A 480V Y 7,80 A

Weight:	: 23 Kg
IE class	: IE3
IP class	: IP66
Isolation class	: F (155°C)
Delta K	: 72 K
IEC frame	: IEC 90
Execution type	: B5 (Flange 200mm)
Shaft Dimensions	: Ø 24 j6 x 50 mm
Cooling	: TEFC - IC411 (Totally Enclosed Fan Cooled)
Duty Cycle:	: S1 100%
Housing material	: Stainless Steel AISI 304
Bearingshield material	: Stainless Steel AISI 304
Shaft material	: Stainless Steel AISI 304 (With Dertec TTS)
Oil seal material	: High Temperature NBR
Bearings A Side (Shaft side)	: 6205 2RS C3 With HTWR Foodgrade Grease
B Side (Fan Side)	: 6205 2RS C3 With HTWR Foodgrade Grease
Cable gland bore	: 2 x M25 for cable Ø between 11 - 15mm)
Cable gland material	: Stainless Steel AISI 304
Thermal protection	: PTC 135 (PTC) : PT1 135 (Clixon / Thermal contact)
Certification	: UL & CE
Taric Code	: 8501200090
Country of origin	: The Netherlands